

Sina HYPE 12 G4

WITH BATTERY SIZE 10



Audio Service

PRODUCT FEATURES

Semi-modular CIC

BASIC FEATURES

Battery compartment as on/off switch

Push button (integrated in battery compartment lid), can be programmed as a program button, program button with on/off function, volume control, Tinnitus noiser level up/down (only with option Wireless)

Level-dependent signal tones/melodies (activate/deactivate) for low battery voltage, program change, on/off function

Audiomatic power-on delay (P) (activate/deactivate)

Wax guard HF 3 Black or HF 4 Black

Microphone filter Microsafe

Removal line

OPTIONS



Audiostreamer Smart Connect

Remote control Smart Remote

Remote control Smart Key

Smart Connect App

Smart Remote App

PROGRAMMING CABLE

Programming cable, right

Art.-No. 105 40 984

Programming cable, left

Art.-No. 105 40 985

TECHNICAL FEATURES

32 signal processing channels / 16 frequency channels

16 AGC channels / 16 MPO channels

6 hearing programs

➤ MusicSelect

Data Logging

Wireless optional

➤ AudioLink

➤ Binaural synchronization

➤ Wireless audio streaming

SIGNAL PROCESSING

Anti-Feedback system

Noise Manager

➤ Adaptive noise reduction

➤ Wiener filter

➤ Impulse suppressor

➤ Auto-situation adaption

Frequency and dynamics concept

➤ TRC S

➤ Selective frequency compression

➤ HiFi functionality

➤ Sound Upgrade (in wireless audio streaming mode)

Programmable Tinnitus function


AUTOMATIC FUNCTIONS

Comfort365


Intelligent Acclimatic

Comformatic

FITTING RANGES



Fitting range 55 dB



Fitting range 65 dB

P = Patent

For more information about features please check out our website www.audioservice.com

Sina HYPE 12 G4

Gain 55 dB





MAXIMUM OUTPUT

Input: 90 dB



MAXIMUM GAIN

Input: 50 dB

IEC 60118-7:2005¹⁾
ANSI S3.22-2009¹⁾



IEC 60118-0²⁾



TECHNICAL INFORMATION

MAXIMUM OUTPUT

| | | |
|------------------------------|--------|--------|
| Peak value at 90 dB | 118 dB | 128 dB |
| 1,600 Hz (RTF) | 110 dB | 118 dB |
| HFA (High Frequency Average) | 112 dB | 115 dB |

FULL ON GAIN

| | | |
|------------------------------|-------|-------|
| Peak value at 50 dB | 55 dB | 66 dB |
| 1,600 Hz (RTF) | 47 dB | 56 dB |
| HFA (High Frequency Average) | 48 dB | 53 dB |
| Reference test gain | 35 dB | 49 dB |

TECHNICAL FEATURES

| | | |
|-----------------------------|----------------|-----------------|
| Battery type | 10 | 10 |
| Battery life in hours | 79 | 79 |
| Frequency range | 100 – 9,000 Hz | 130 – 10,000 Hz |
| Battery current consumption | 0.80 mA | 0.80 mA |
| Equivalent noise level | 19 dB | 22 dB |
| Tinnitus noiser broadband | 75 dB | |
| Distortion | | |
| 500 Hz | 1% | 2% |
| 800 Hz | 1% | 2% |
| 1,600 Hz | 1% | 1% |

¹⁾ Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler

²⁾ Technical data measured in accordance with IEC 60118-0 at ear simulator



WARNING

Small parts present a choking hazard.

This device is not suitable for fitting to babies, small children or mentally disabled persons.

Sina HYPE 12 G4

Gain 65 dB





MAXIMUM OUTPUT

Input: 90 dB



MAXIMUM GAIN

Input: 50 dB

IEC 60118-7:2005¹⁾
ANSI S3.22-2009¹⁾



IEC 60118-0²⁾



TECHNICAL INFORMATION

MAXIMUM OUTPUT

| | | |
|------------------------------|--------|--------|
| Peak value at 90 dB | 124 dB | 134 dB |
| 1,600 Hz (RTF) | 117 dB | 124 dB |
| HFA (High Frequency Average) | 118 dB | 122 dB |

FULL ON GAIN

| | | |
|------------------------------|-------|-------|
| Peak value at 50 dB | 65 dB | 75 dB |
| 1,600 Hz (RTF) | 60 dB | 65 dB |
| HFA (High Frequency Average) | 61 dB | 67 dB |
| Reference test gain | 41 dB | 60 dB |

TECHNICAL FEATURES

| | | |
|-----------------------------|----------------|----------------|
| Battery type | 10 | 10 |
| Battery life in hours | 63 | 63 |
| Frequency range | 100 – 6,300 Hz | 100 – 7,900 Hz |
| Battery current consumption | 1.00 mA | 1.00 mA |
| Equivalent noise level | 17 dB | 15 dB |
| Tinnitus noiser broadband | 80 dB | |
| Distortion | | |
| 500 Hz | 2% | 3% |
| 800 Hz | 2% | 3% |
| 1,600 Hz | 1% | 2% |

¹⁾ Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler

²⁾ Technical data measured in accordance with IEC 60118-0 at ear simulator



WARNING Small parts present a choking hazard.
This device is not suitable for fitting to babies, small children or mentally disabled persons.



WARNING The maximum output levels of the hearing systems can reach or exceed 132 dB SPL.
Risk of injury to the hearing of the wearer. Ensure that the hearing systems are fitted with care.

For control ranges and more programming features see Hearing Instrument Simulation of Connexx 8.2 and AudioFit 8.2 or higher.

AS AUDIO-SERVICE GmbH · Alter Postweg 190 · 32584 Löhne · Germany
info@audioservice.com · www.audioservice.com