

Sun Li-Ion 12 G4

RECEIVER-IN-CANAL HEARING SYSTEM (RIC) WITH LITHIUM-ION BATTERY



PRODUCT FEATURES

Receiver-in-Canal hearing system (RIC) with external receiver
For open and closed fitting

BASIC FEATURES

Battery with lithium-ion technology
Push button, can be programmed as a program button, volume control, Tinnitus noiser level up/down
Level-dependent signal tones/melodies (activate/deactivate) for low battery voltage, program change, volume control
Telephone coil
Audiomatic power-on delay (P) (activate/deactivate)
IP68-certified

OPTIONS



Smart Li-Ion Power (compulsory)
Audiostreamer Smart Connect
Remote Control Smart Remote
Remote Control Smart Key
Smart Connect App, with AudioDirSelect
Smart Remote App, with AudioDir Select
External receiver S with FOG = 45 dB¹⁾
External receiver M with FOG = 60 dB¹⁾
External receiver P with FOG = 70 dB^{1) 2)}
Customized CLIC MOULD 2.0 (Open or Power)
Click Domes (Open, Semi-open, Closed or Double)
Click Sleeves (Open or Closed)
AutoPhone set

PROGRAMMING CABLE

Cable for HiPro interface, right	Art. No. 029 44 986
Cable for HiPro interface, left	Art. No. 029 44 994
Cable for Noah-Link interface, right	Art. No. 106 02 843
Cable for Noah-Link interface, left	Art. No. 106 02 842

HOUSING COLORS

Beige	Dark gray	Granite
Tobacco	Silver	Bronze
Gray	Pearly-white	

TECHNICAL FEATURES

32 signal processing channels / 16 frequency channels
16 AGC channels / 16 MPO channels
6 hearing programs
 > MusicSelect
 > ZearPhone
 Data Logging
 Wireless
 > AudioLink
 > Binaural synchronization
 > Wireless audio streaming optional
 > CROS/BiCROS

SIGNAL PROCESSING


Anti-Feedback system
Noise Manager
 > Adaptive noise reduction
 > Wiener filter
 > Adaptive wind noise reduction
 > Impulse suppressor
 > Auto-situation adaption
 > Selectronic
 AudioTronic multi-microphone system
 > Panorama
 > Directional static
 > Automatic
 > Adaptive
 > Language 360
 > AudioSpot
 Frequency and dynamics concept
 > TRC S
 > Selective frequency compression
 > Sound Upgrade (in wireless audio streaming mode)

PROGRAMMABLE TINNITUS FUNCTION


AUTOMATIC FUNCTIONS

Comfort365
Intelligent Acclimatic
Comformatic


FITTING RANGES



Fitting range external receiver 45 dB



Fitting range external receiver 60 dB



Fitting range external receiver 70 dB²⁾

¹⁾ measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009
²⁾ 70 dB measured with CLIC MOULD 2.0, values vary if domes are used for fitting
P = Patent

Sun Li-Ion 12 G4

Gain 45 dB





MAXIMUM OUTPUT

Input: 90 dB



MAXIMUM GAIN

Input: 50 dB

IEC 60118-7:2005³⁾
ANSI S3.22-2009³⁾



IEC 60118-0⁴⁾



TECHNICAL INFORMATION

SATURATION OSPL 90

Peak value at 90 dB	108 dB	119 dB
1,600 Hz (RTF)	100 dB	109 dB
HFA (High Frequency Average)	100 dB	106 dB

FULL ON GAIN

Peak value at 50 dB	45 dB	56 dB
1,600 Hz (RTF)	34 dB	42 dB
HFA (High Frequency Average)	36 dB	41 dB
Reference test gain	23 dB	33 dB

TECHNICAL FEATURES

Battery type	Lithium-ion battery	Lithium-ion battery
Service life of the charged battery in hours	28	28
Frequency range	100 – 8,200 Hz	100 – 8,300 Hz
Battery current consumption	0.90 mA	0.90 mA
Equivalent noise level	18 dB	22 dB
Tinnitus noiser broadband	65 dB	
Telecoil sensitivity (1 mA/m)	68 dB	75 dB
Distortion		
500 Hz	1%	1%
800 Hz	1%	1%
1,600 Hz	1%	2%

³⁾ Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler

⁴⁾ Technical data measured in accordance with IEC 60118-0 at ear simulator



WARNING

Small parts present a choking hazard.

This device is not suitable for fitting to babies, small children or mentally disabled persons.

Sun Li-Ion 12 G4

Gain 60 dB



Audio Service



MAXIMUM OUTPUT

Input: 90 dB



MAXIMUM GAIN

Input: 50 dB

IEC 60118-7:2005³⁾
ANSI S3.22-2009³⁾



IEC 60118-0⁴⁾



TECHNICAL INFORMATION

SATURATION OSPL 90

Peak value at 90 dB	119 dB	129 dB
1,600 Hz (RTF)	113 dB	122 dB
HFA (High Frequency Average)	113 dB	116 dB

FULL ON GAIN

Peak value at 50 dB	60 dB	70 dB
1,600 Hz (RTF)	46 dB	54 dB
HFA (High Frequency Average)	50 dB	53 dB
Reference test gain	36 dB	47 dB

TECHNICAL FEATURES

Battery type	Lithium-ion battery	Lithium-ion battery
Service life of the charged battery in hours	27	27
Frequency range	100 – 8,200 Hz	100 – 8,300 Hz
Battery current consumption	1.00 mA	1.00 mA
Equivalent noise level	19 dB	23 dB
Tinnitus noiser broadband	70 dB	
Telecoil sensitivity (1 mA/m)	80 dB	85 dB
Distortion		
500 Hz	1%	1%
800 Hz	1%	3%
1,600 Hz	2%	3%

³⁾ Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler

⁴⁾ Technical data measured in accordance with IEC 60118-0 at ear simulator



WARNING

Small parts present a choking hazard.

This device is not suitable for fitting to babies, small children or mentally disabled persons.

Sun Li-Ion 12 G4

Gain 70 dB²⁾





MAXIMUM OUTPUT

Input: 90 dB



MAXIMUM GAIN

Input: 50 dB

IEC 60118-7:2005³⁾
ANSI S3.22-2009³⁾



IEC 60118-0⁴⁾



TECHNICAL INFORMATION

SATURATION OSPL 90

Peak value at 90 dB	124 dB	134 dB
1,600 Hz (RTF)	118 dB	127 dB
HFA (High Frequency Average)	118 dB	122 dB

FULL ON GAIN

Peak value at 50 dB	70 dB	80 dB
1,600 Hz (RTF)	60 dB	67 dB
HFA (High Frequency Average)	62 dB	65 dB
Reference test gain	41 dB	52 dB

TECHNICAL FEATURES

Battery type	Lithium-ion battery	Lithium-ion battery
Service life of the charged battery in hours	27	27
Frequency range	100 – 7,800 Hz	100 – 7,800 Hz
Battery current consumption	1.00 mA	1.00 mA
Equivalent noise level	18 dB	21 dB
Tinnitus noiser broadband	75 dB	
Telecoil sensitivity (1 mA/m)	91 dB	100 dB
Distortion		
500 Hz	2%	3%
800 Hz	2%	3%
1,600 Hz	1%	2%

²⁾ 70 dB measured with CLIC MOULD 2.0, values vary if domes are used for fitting

³⁾ Technical data measured in accordance with IEC 60118-7:2005 and ANSI S3.22-2009 at 2 ccm coupler

⁴⁾ Technical data measured in accordance with IEC 60118-0 at ear simulator



WARNING

Small parts present a choking hazard.
This device is not suitable for fitting to babies, small children or mentally disabled persons.



WARNING

The maximum output levels of the hearing systems can reach or exceed 132 dB SPL.
Risk of injury to the hearing of the wearer. Ensure that the hearing systems are fitted with care.

For control ranges and more programming features see Hearing Instrument Simulation of Connex 8.3 and AudioFit 8.3 or higher.

AS AUDIO-SERVICE GmbH · Alter Postweg 190 · 32584 Löhne · Germany
info@audioservice.com · www.audioservice.com